

Declaration of Performance No. tona-BIIa-001

1: Unique identification code of the product type:

Dry-pressed ceramic tiles, with water absorption 3%<Eb≤6%

2: Intended use(s) :

For internal wall and floorings

3: Name or registered trade mark, and conctact address of the manufacter:

Tonalite S.p.A.

Via Costa 8, 40019 Sant'Agata Bolognese - Italia

4: System(s) of assessment and verification of constancy of performance (AVCP) : Systems 4

5: Name and identification number of notified laboratory, if relevant: Not relevant

6: Declared performances

<u>Essential characteristics</u>	<u>Performance</u>	Harmonised technical specification	
Reaction to fire	A1 - A1FL		
Release of dangerous substance, for:		-	
Cadmium	NPD		
Lead	NPD		
Breaking strength :			
$Thickness \ge 7.5mm$	>1000 N	1	
Thickness < 7.5mm	>600 N	EN 14411:2012	
Slipperiness	See table attached		
Tactility	NPD		
Bond strength/adhesion, for:			
Cementitious adhesive, type C2	NPD		
Thermal shock resistance	NPD		
Durability for:			
Internal use	Pass		
External use: freeze-thaw resistance	NPD		

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacterer by :

Eng. Pagani Paolo Production Manager

Place and date of issue

Signature

Sant'Agata Bolognese 27/06/13

Table – Slipperiness (where required by regulation)					
		DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	DOCUMENTO BASICO SUA (ESP)	
Test method used		Ramp	Tortus	Pendulum	
Series	Formato	Performance value/class			
COLORANDA			>0,40		
COTTO D'ARTE		NPD	NPD	NPD	
DIAMANTE		NPD	NPD	NPD	
EGEA		R9			
EOLIE		NPD	NPD	NPD	
EXABRIGHT		NPD	NPD	NPD	
FLORENCE		NPD	NPD	NPD	
FONDALI		NPD	NPD	NPD	
KRAKLE'		NPD	NPD	NPD	
LUX		NPD	NPD	NPD	
MIRO'		NPD	NPD	NPD	
ORIZZONTI		NPD	NPD	NPD	
PORTOFINO		NPD	NPD	NPD	
PROVENZALE		NPD	NPD	NPD	
SATIN		NPD	NPD	NPD	
SILK		NPD	NPD	NPD	
SOLEIL		NPD	NPD	NPD	