

PLATFORM | SURFACES

TECHNICAL DATA SHEET FOR MASTERMIND CROSS + STAR

a) DIMENSIONS

Characteristic	Norm	Average value	
<i>Length and width</i>	EN ISO 10545-2	$\pm 0.6 \%$	$\pm 2.0 \text{ mm}$
<i>Thickness</i>	EN ISO 10545-2	$\pm 5 \%$	$\pm 0.5 \text{ mm}$
<i>Straightness of sides</i>	EN ISO 10545-2	$\pm 0.5 \%$	$\pm 1.5 \text{ mm}$
<i>Rectangularity</i>	EN ISO 10545-2	$\pm 0.5 \%$	$\pm 2.0 \text{ mm}$
<i>Surface flatness</i>			
<i>Central curvature</i>	EN ISO 10545-2	$\pm 0.5 \%$	$\pm 2.0 \text{ mm}$
<i>Side curvature</i>		$\pm 0.5 \%$	$\pm 2.0 \text{ mm}$
<i>Warp</i>		$\pm 0.5 \%$	$\pm 2.0 \text{ mm}$

b) PHYSICAL PROPERTIES

Characteristic	Norm	Average value
<i>Water absorption</i>	EN ISO 10545-3	< 0.5 % (BI_a)
<i>Breaking of rupture</i>	EN ISO 10545-4	> 1300 N
<i>Modulus of rupture</i>	EN ISO 10545-4	> 35 N/mm ²
<i>Resistance to surface abrasion (PEI)</i>	EN ISO 10545-7	4
<i>Scracth hardness (MOHS)</i>	EN 101	7
<i>Linear thermal expansion coefficient</i>	EN ISO 10545-8	$6.5*10^{-6} /^\circ\text{C}$
<i>Resistance to termal shock</i>	EN ISO 10545-9	Guaranteed
<i>Crazing resistance</i>	EN ISO 10545-11 ASTM C424	Guaranteed
<i>Frost resistance</i>	EN ISO 10545-12	Guaranteed
<i>Slip resistance</i>		
<i>Ramp test (shoes)</i>	DIN 51130	R9
<i>Ramp test (bare foot)</i>	DIN 51097	B
<i>Pendulum test</i>	UNE ENV 12633	Clase 2
<i>Pendulum test</i>	BS EN 13036-4:2011	40
<i>Coefficient of Friction DCOF(wet)</i>	ASTM BOT3000	≥ 0.42
<i>Coefficient of Friction (wet)</i>	ASTM C-1028	≥ 0.50
<i>Coefficient of Friction</i>	B.C.R.A. Method	$\mu \geq 0.4$
<i>Shade Variation</i>	---	V2
<i>Reaction to fire</i>	---	A1 _{FL} - s1 / A1- s1, d0

PLATFORM | SURFACES

TECHNICAL DATA SHEET FOR MASTERMIND CROSS + STAR

c) CHEMICAL PROPERTIES

<i>Characteristic</i>	<i>Norm</i>	<i>Average value</i>
<i>Resistance to stains</i>	EN ISO 10545-14	5
<i>Chemical resistance</i>		
<i>Low concentration acids and alkalis</i>		GLA
<i>High concentration acids and alkalis</i>	EN ISO 10545-13	GHA
<i>Household chemicals</i>		GA

PLATFORM | SURFACES

TECHNICAL DATA SHEET FOR MASTERMIND HEX

a) DIMENSIONS

Characteristic	Norm	Average value
<i>Length and width</i>	EN ISO 10545-2	$\pm 0.6 \%$ $\pm 2.0 \text{ mm}$
<i>Thickness</i>	EN ISO 10545-2	$\pm 5 \%$ $\pm 0.5 \text{ mm}$
<i>Straightness of sides</i>	EN ISO 10545-2	$\pm 0.5 \%$ $\pm 1.5 \text{ mm}$
<i>Rectangularity</i>	EN ISO 10545-2	$\pm 0.5 \%$ $\pm 2.0 \text{ mm}$
<i>Surface flatness</i>		
<i>Central curvature</i>	EN ISO 10545-2	$\pm 0.5 \%$ $\pm 2.0 \text{ mm}$
<i>Side curvature</i>		$\pm 0.5 \%$ $\pm 2.0 \text{ mm}$
<i>Warp</i>		$\pm 0.5 \%$ $\pm 2.0 \text{ mm}$

b) PHYSICAL PROPERTIES

Characteristic	Norm	Average value
<i>Water absorption</i>	EN ISO 10545-3	< 0.5 % (BI_a)
<i>Breaking of rupture</i>	EN ISO 10545-4	> 1300 N
<i>Modulus of rupture</i>	EN ISO 10545-4	> 35 N/mm ²
<i>Resistance to surface abrasion (PEI)</i>	EN ISO 10545-7	4 (Black 2)
<i>Scracth hardness (MOHS)</i>	EN 101	7
<i>Linear thermal expansion coefficient</i>	EN ISO 10545-8	$6.5 \cdot 10^{-6} /^\circ\text{C}$
<i>Resistance to termal shock</i>	EN ISO 10545-9	Guaranteed
<i>Crazing resistance</i>	EN ISO 10545-11 ASTM C424	Guaranteed
<i>Frost resistance</i>	EN ISO 10545-12	Guaranteed
<i>Slip resistance</i>		
<i>Ramp test (shoes)</i>	DIN 51130	R9
<i>Ramp test (bare foot)</i>	DIN 51097	B
<i>Pendulum test</i>	UNE ENV 12633	Class 2
<i>Pendulum test</i>	BS EN 13036-4:2011	40
<i>Coefficient of Friction DCOF(wet)</i>	ASTM BOT3000	≥ 0.42
<i>Coefficient of Friction DCOF (wet)</i>	ASTM C-1028	≥ 0.50
<i>Coefficient of Friction</i>	B.C.R.A. Method	$\mu \geq 0.4$

PLATFORM | SURFACES

TECHNICAL DATA SHEET FOR MASTERMIND HEX

Characteristic	Norm	Average value
Slight color differences	EN ISO 10545-16	$\Delta E_{cmc} < 0.75$
Reaction to fire	---	A1 _{FL} - s1 / A1- s1, d0
Shade Variation	---	V2

c) PROPIEDADES QUÍMICAS – CHEMICAL PROPERTIES

Characteristic	Norm	Average value
Resistance to stains	EN ISO 10545-14	5
Chemical resistance		
Low concentration acids and alkalis		GLA
High concentration acids and alkalis	EN ISO 10545-13	GHA
Household chemicals		GA